

Elastomeric Thermal Insulation Design Considerations in Long, Aluminized Solid Rocket Motors

Heath T. Martin

An all-new sounding rocket was designed at NASA's Marshall Space Flight Center that featured an aft finocyl, aluminized solid propellant grain and silica-filled ethylene-propylene-diene monomer (SFEPDM) internal insulation. Upon the initial static firing of the first of this new design, the solid rocket motor (SRM) case failed thermally just upstream of the aft closure early in the burn time. Subsequent fluid modeling indicated that the high-velocity combustion-product jets emanating from the fin-slots in the propellant grain were likely inducing a strongly swirling flow, thus substantially increasing the severity of the convective environment on the exposed portion of the SFEPDM insulation in this region. The aft portion of the fin-slots in another of the motors were filled with propellant to eliminate the possibility of both direct jet impingement on the exposed SFEPDM and the appearance of strongly swirling flow in the aft region of the motor. When static-fired, this motor's case still failed in the same axial location, and, though somewhat later than for the first static firing, still in less than 1/3rd of the desired burn duration. These results indicate that the extreme material decomposition rates of the SFEPDM in this application are not due to gas-phase convection or shear but rather to interactions with burning aluminum or alumina slag. Further comparisons with between SFEPDM performance in this design and that in other hot-fire tests provide insight into the mechanisms of SFEPDM decomposition in SRM aft domes that can guide the upcoming redesign effort, as well as other future SRM designs. These data also highlight the current limitations of modeling elastomeric insulators solely with diffusion-controlled, gas-phase thermochemistry in SRM regions with significant viscous shear and/or condense-phase impingement or flow.

| | | |
|--|-------------|--|
| For ERG Use Only: | Paper #: | Paper ID: |
| PLEASE DOWNLOAD & SAVE THIS BLANK FORM BEFORE COMPLETING. | | |
| Abstract Submittal Form | | JANNAF 64th JPM / PIB / 44th SMBS / 40th PEDCS / 31st RNTS / 29th SEPS Joint Subcommittee Meeting May 2017 |
| Abstract Due Date: Monday, 19 December 2016 | | Fields with an asterisk (*) are required. |
| <input type="checkbox"/> Check here if you are submitting an abstract because you have been INVITED to participate in a Specialist Session or Workshop. If so, who is the Chair? | | |
| * Title: Elastomeric Thermal Insulation Design Considerations in Long, Aluminized Solid Rocket Motors | | |
| * Submitted to: <input type="checkbox"/> JPM <input type="checkbox"/> PIB <input type="checkbox"/> SMBS <input type="checkbox"/> PEDCS <input checked="" type="checkbox"/> RNTS <input type="checkbox"/> SEPS Please select ONE subcommittee. | | |
| Refer to Call for Papers for description of Subcommittee Mission Areas and select one from the choices below. | | |
| * Mission Area : <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4 <input type="checkbox"/> 5 <input type="checkbox"/> 6 <input type="checkbox"/> 7 <input type="checkbox"/> 8 <input type="checkbox"/> 9 <input type="checkbox"/> 10 | | |
| * Updated Paper? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No | | * Student Paper? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No |
| Sponsoring organization if SBIR-funded: | | |
| IF MORE THAN 4 AUTHORS, PLACE THEIR <u>COMPLETE</u> CONTACT INFORMATION (as requested below) ON P.2 AFTER ABSTRACT TEXT. | | |
| Primary Author (NOTE: will receive all correspondence regarding participation in this program and is assumed to be presenter) | | |
| * Name: Heath T. Martin | | * U.S. Citizen <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No |
| * Organization (contractors provide company name): National Aeronautics Space Administration - Marshall Space Flight Center | | |
| * Address: Building 4203/Rm 3151, ER43 | | |
| * City: Huntsville | * State: AL | * ZIP Code: 35812 |
| * Phone: 256-544-5993 | Fax: | * Email: heath.t.martin@nasa.gov |
| 2nd Author Please provide <u>full contact information</u> for each author. | | |
| Name: | | * U.S. Citizen <input type="checkbox"/> Yes <input type="checkbox"/> No |
| Organization (contractors provide company name): | | |
| Address: | | |
| City: | State: | ZIP Code: |
| Phone: | Fax: | Email: |
| 3rd Author Please provide <u>full contact information</u> for each author. | | |
| Name: | | * U.S. Citizen <input type="checkbox"/> Yes <input type="checkbox"/> No |
| Organization (contractors provide company name): | | |
| Address: | | |
| City: | State: | ZIP Code: |
| Phone: | Fax: | Email: |
| 4th Author Please provide <u>full contact information</u> for each author. | | |
| Name: | | * U.S. Citizen <input type="checkbox"/> Yes <input type="checkbox"/> No |
| Organization (contractors provide company name): | | |
| Address: | | |
| City: | State: | ZIP Code: |
| Phone: | Fax: | Email: |
| <input type="checkbox"/> Check this box if you are listing additional authors on page 2 after the abstract. | | |
| * Management Support | | * Presenting Author / U.S. Citizenship |

| | |
|--|--|
| <input checked="" type="checkbox"/> Author(s) has confirmed management support (i.e., required resources) to prepare, submit, and present this paper at the above subject JANNAF Meeting. | The presenting author for this paper will be ERG must be notified of any change to the presenting author immediately. Presenter must be a U.S. Citizen; attendance at this meeting is restricted to U.S. Citizens. |
| For ERG Use Only: Paper #: Paper ID: | |
| Abstract Submittal Form <div style="float: right; text-align: right;"> JANNAF 64th JPM / PIB / 44th SMBS / 40th PEDCS / 31st RNTS / 29th SEPS Joint Subcommittee Meeting May 2017 </div> | |
| Abstract Due Date: Monday, 19 December 2016 Fields with an asterisk (*) are required. | |
| Unclassified Abstract (250 – 300 words; do not include figures or tables) | |
| <p>* An all-new sounding rocket was designed at NASA's Marshall Space Flight Center that featured an aft finocyl, aluminized solid propellant grain and silica-filled ethylene-propylene-diene monomer (SFEPDM) internal insulation. Upon the initial static firing of the first of this new design, the solid rocket motor (SRM) case failed thermally just upstream of the aft closure early in the burn time. Subsequent fluid modeling indicated that the high-velocity combustion-product jets emanating from the fin-slots in the propellant grain were likely inducing a strongly swirling flow, thus substantially increasing the severity of the convective environment on the exposed portion of the SFEPDM insulation in this region. The aft portion of the fin-slots in another of the motors were filled with propellant to eliminate the possibility of both direct jet impingement on the exposed SFEPDM and the appearance of strongly swirling flow in the aft region of the motor. When static-fired, this motor's case still failed in the same axial location, and, though somewhat later than for the first static firing, still in less than 1/3rd of the desired burn duration. These results indicate that the extreme material decomposition rates of the SFEPDM in this application are not due to gas-phase convection or shear but rather to interactions with burning aluminum or alumina slag. Further comparisons with between SFEPDM performance in this design and that in other hot-fire tests provide insight into the mechanisms of SFEPDM decomposition in SRM aft domes that can guide the upcoming redesign effort, as well as other future SRM designs. These data also highlight the current limitations of modeling elastomeric insulators solely with diffusion-controlled, gas-phase thermochemistry in SRM regions with significant viscous shear and/or condense-phase impingement or flow.</p> | |
| Audio-Visual Requirements and Room Setup | |
| <p>Standard equipment supplied in each meeting room includes: Laptop (with sound), LCD Projector (minimum 1024 x 768 native resolution and 4500 lumens), Screen, Podium Microphone, Wireless Lavalier Microphone. Rooms are typically set in "Theater" style (rows of chairs). If your presentation requires any unusual A-V equipment or set-up, please indicate those requirements below.</p> <p>Enter any unusual A-V or room setup requirements here. First check the list of standard equipment and typical room setup described above. This section will EXPAND to accommodate your text.</p> | |
| <div style="background-color: yellow; border: 1px solid black; padding: 5px; margin-bottom: 5px;"> ➤ If your abstract is anything other than Distribution Statement A, you must upload both pages of this completed form to the CPIAC/JANNAF secure website. Upload instructions can be found in the Call for Papers on page 3. </div> <div style="border: 1px solid black; padding: 5px;"> ➤ Distribution Statement A abstracts may be uploaded or emailed. ➤ By submitting an abstract, you agree to both complete a final paper for publication and to attend the meeting to present this information. ➤ Direct questions to Shelley Cohen, by phone at 410.992.7302 x 215, or email to scohen@erg.jhu.edu. </div> | |

Form Date: 11/1/16